



## WDE-603T

### Commercial Dehumidifier

#### Features:

- Rotary compressor
- Standard colour sheet metal casing,
- Automatic defrost
- Universal wheels
- Humidity setting
- Sensor fault indicator function
- Three-minute automatic delay protection of the compressor
- Washable filter
- With 7 ltrs. Tank.
- Continuous drainage option available.
- Automatic humidistat Control.
- Portable easy to carry handle; Easily move on wheels.

#### Technical Specification: -

- |  |   |   |
|--|---|---|
| • Model No.:                             | - | WDE-603T  |
| • Moisture removal 30°C, 80%R.H.:        | - | 60L/Day   |
| • Power supply V/Hz:                     | - | 220~240V/50Hz                                   |
| • Rated Power consumption 30°C, 80%R.H.: | - | 820W  |
| • Control Type:-                         |   | Electric  |
| • Maintain level:                        | - | 30% R.H.- 80% R.H.                              |
| • Current 30°C, 80%R.H.:                 | - | 3.5A  |
| • Air flow/Air Circulation:              | - | 550m <sup>3</sup> /hr                           |
| • Ambient Temperature for operation:     | - | 5-38°C  |
| • Water tank capacity:                   | - | 7 Litres  |
| • Approx. Cover Area*:                   | - | 50~120m <sup>2</sup> (height=2.6m)              |
| • Noise level:                           | - | 60 dB(A)  |
| • Refrigerant:                           | - | R410  |
| • Net Weight:                            | - | 35 kgs  |
| • Body dimensions (H x W x D):           | - | 680 x 372 x 394 mm / 26.77 x 14.65 x 15.51 inch |